

# **Wind Direction Transmitter Compact**

Part number: 4.3129.60.x01

Measuring transmitter for the measurement of the horizontal wind direction with serial output signal. The wind vane consists of fibre-glass reinforced, the housing is made of anodised aluminium and plastic.

The instrument has a threaded pin PG 21 with 2 nuts for mounting.



# **Specification**

Part number: 4.3129.60.x01

| rait number. 4.3123.00.x01 |                        |
|----------------------------|------------------------|
| Wind direction             |                        |
| Measuring range            | 0 360 °                |
| Resolution                 | 0.35 °                 |
| Accuracy                   | ±1°                    |
| Data output digital        |                        |
| Output type                | 10-bit serial synchron |
| Operating voltage          |                        |
| Electronic                 | 3.3 30 V DC            |
| Current consumption        | 1 mA                   |
| Heating                    | 24 V AC/DC, max 20 W   |
| General                    |                        |
| Ambient temp.              | -50 +70 °C             |
| Protection                 | IP 55                  |
|                            |                        |

### **Versions**

As per 4.3129.60.x01, but:

Product number 4.3129.60.701

General



| Electr. connection | 7 - pol plug   |
|--------------------|----------------|
| Dimension          | Ø 330 x 270 mm |
| Weight             | 0.4 kg         |

#### Product number 4.3129.60.001

| General            |  |
|--------------------|--|
| Electr. connection | 12 m cable LiYCY<br>6 x 0.25 mm <sup>2</sup> |
| Dimension          | Ø 330 x 220 mm                               |
| Weight             | 1.1 kg                                       |

## **Accessories**

| Product | Product name  | Brief description   |                              |
|---------|---|---|------------------------------|
|         | Traverse compact for wall mounting 4.3171.2x.000              | For storefront mounting of a  | measuring value transmitter. |
|         |   | General   |                              |
|         |   | Material  | Aluminium                    |
|         |   |   |                              |
|         | Traverse for Wind<br>Transmitters<br>Compact<br>4.3171.3x.000 | For mounting the wind transmitter and wind direction transmitter jointly onto a mast. |                              |
|         |   | Material  |                              |
|         |   | Traverse  | aluminium (AlMgSi0.5)        |
|         |   | Gripping clamb  | stainless steel              |
|         |   | General   |                              |
|         |   | Sensor distance horizontal  | 0.8 m                        |
|         |   | Weight  | 0.35 kg                      |
|         |   | Mounting  | hole Ø 29 mm                 |
|         |   |   |                              |
|         |   |   |                              |





Traverse short for Wind Transmitters Compact 4.3171.4x.000

For mounting one wind transmitter or wind direction transmitter at a mast.

| Material                   |                       |
|----------------------------|-----------------------|
| Traverse                   | aluminium (AlMgSi0.5) |
| Gripping clamb             | stainless steel       |
| General                    |                       |
| Sensor distance horizontal | 0.4 m                 |
| Weight                     | 0.3 kg                |
| Mounting                   | hole Ø 29 mm          |



Holder compact 506347

The holder serves for the mounting of a wind transmitter, Compact-type, onto an instrument carrier or mast.

| General   |                           |                           |  |
|-----------|---------------------------|---------------------------|--|
| Mounting  | for mast tubes Ø 35 50 mm | for mast tubes Ø 35 50 mm |  |
| Material  | stainless steel (V2A)     |                           |  |
| Dimension | 80 x 150 mm               |                           |  |
| Weight    | 0.35 kg                   |                           |  |
| Mounting  | hole Ø 32.5 mm            |                           |  |