

# Wind Direction Transmitter Compact

**Part number: 4.3129.60.x01**

Measuring transmitter for the measurement of the horizontal wind direction with serial output signal. The wind vane consists of fibre-glass reinforced, the housing is made of anodised aluminium and plastic.  
The instrument has a threaded pin PG 21 with 2 nuts for mounting.



## Specification

**Part number: 4.3129.60.x01**

<b>Wind direction</b>	
Measuring range	0 ... 360 °
Resolution	0.35 °
Accuracy	±1,5 °
<b>Data output digital</b>	
Output type	10-bit serial synchron
<b>Operating voltage</b>	
Electronic	3.3 ... 30 V DC
Current consumption	1 mA
Heating	24 V AC/DC, max 20 W
<b>General</b>	
Ambient temp.	-50 ... +70 °C
Protection	IP 55

## Versions

As per 4.3129.60.x01, but:

**Product number 4.3129.60.701**



<b>General</b>
----------------

Electr. connection	7 - pol plug
Dimension	Ø 330 x 270 mm
Weight	0.4 kg

Product number 4.3129.60.001

General	
Electr. connection	12 m cable LiYCY 6 x 0.25 mm²
Dimension	Ø 330 x 220 mm
Weight	1.1 kg

Accessories

Product	Product name	Brief description	
	Traverse compact for wall mounting 4.3171.2x.000	For storefront mounting of a measuring value transmitter.	
		General	
		Material	Aluminium
	Traverse for Wind Transmitters Compact 4.3171.3x.000	For mounting the wind transmitter and wind direction transmitter jointly onto a mast.	
		Material	
		Traverse	aluminium (AlMgSi0.5)
		Gripping clamb	stainless steel
		General	
		Sensor distance horizontal	0.8 m
		Weight	0.35 kg
		Mounting	hole Ø 29 mm



Traverse short for  
Wind Transmitters  
Compact  
4.3171.4x.000

For mounting one wind transmitter or wind direction transmitter at a mast.

#### Material

Traverse	aluminium (AlMgSi0.5)
Gripping clamb	stainless steel

#### General

Sensor distance horizontal	0.4 m
Weight	0.3 kg
Mounting	hole Ø 29 mm



Geovane  
4.3190.00.900

The product set combines the precise wind vanes from Thies CLIMA with the advanced Geovane from Kintech Engineering. The Geovane uses GPS and the sun position to automatically determine the exact north direction 1° accurate. This combination ensures the highest accuracy of wind direction against the geographic north point as a reference.

- Geovane for automatic north correction
- 1° precise wind vanes from Thies CLIMA
- Wind vane and geovane are preconfigured
- Ideal e.g. for site surveys, power curve monitoring and meteorology

#### Wind direction

Measuring range	0 ... 380 °
Resolution	0.06° RS-485 0.11° Analog voltage outputs 0.06... 0.16° Frequency output
Accuracy	1°

#### Miscellaneous

Electrical input	0 ... 30 V
------------------	------------

#### Operating voltage

Electronic	6 ... 12 V DC
------------	---------------

#### General

Ambient temp.	-25 ... +85 °C
Mounting	Onto mast tube Ø34mm
Protection	IP 67
Measuring time	1, 5, 10, 30, 60 seconds
Weight	0,815 kg



Holder compact  
506347

The holder serves for the mounting of a wind transmitter, Compact-type, onto an instrument carrier or mast.

General	
Mounting	for mast tubes Ø 35 ... 50 mm
Material	stainless steel (V2A)
Dimension	80 x 150 mm
Weight	0.35 kg
Mounting	hole Ø 32.5 mm