

Wind Direction Transmitter Compact

Part number: 4.3129.00.712
Measuring transmitter for the measurement of the horizontal wind direction with Potentiometer-output. The wind vane consists of fibre-glass reinforced, the housing is made of anodised aluminium and plastic.
The instrument has a threaded pin PG 21 with 2 nuts for mounting.



Specification




Part number: 4.3129.00.712	
Wind direction	
Measuring range	0 ... 360 °
Resolution	0.5 °
Accuracy	±2 °
Data output analog	
Wind direction	0 ... 2 kê
Operating voltage	
Electronic	0 ... 24 V DC max. load 1 mA
Heating	24 V AC/DC, max 20 W
General	
Ambient temp.	-40 ... +70 °C
Electr. connection	7 - pole plug
Protection	IP 55
Dimension	Ø 330 x 270 mm
Weight	0.4 kg

Versions

As per 4.3129.00.712, but:

Product number 4.3129.10.712	
Operating voltage	
Heating	without heating

Accessories

Product	Product name	Brief description	
	Traverse compact for wall mounting 4.3171.2x.000	For storefront mounting of a measuring value transmitter.	
		General	
		Material	Aluminium
	Traverse for Wind Transmitters Compact 4.3171.3x.000	For mounting the wind transmitter and wind direction transmitter jointly onto a mast.	
		Material	
		Traverse	aluminium (AlMgSi0.5)
		Gripping clamb	stainless steel
		General	
		Sensor distance horizontal	0.8 m
		Weight	0.35 kg
		Mounting	hole Ø 29 mm
	Traverse short for Wind Transmitters Compact 4.3171.4x.000	For mounting one wind transmitter or wind direction transmitter at a mast.	
		Material	
		Traverse	aluminium (AlMgSi0.5)
		Gripping clamb	stainless steel
		General	
		Sensor distance horizontal	0.4 m
		Weight	0.3 kg
		Mounting	hole Ø 29 mm



Holder compact
506347

The holder serves for the mounting of a wind transmitter, Compact-type, onto an instrument carrier or mast.

General	
Mounting	for mast tubes Ø 35 ... 50 mm
Material	stainless steel (V2A)
Dimension	80 x 150 mm
Weight	0.35 kg
Mounting	hole Ø 32.5 mm