

## Small Wind Transmitter

**Part number: 4.3515.5x.xxx**

Measuring instrument for the direction-independent measurement of the horizontal air flow in the open. The sensor is a small construction with a Reed-contact, which is activated by the revolution of the cup star. The housing is made of synthetic material.



## Specification

**Part number: 4.3515.5x.xxx**

### Wind speed

Measuring range	0.9 ... 40 m/s
Resolution	0.4 m wind run
Accuracy	±0.5 m/s or ±5 % of meas. value

### Data output digital

Frequency	100 Hz @ 40 m/s
Output type	reed - contact
Contact load	10 W, max. 42 V DC, max. 0.4 A

### General

Ambient temp.	-25 ... +60 °C, ice-free
Electr. connection	3 m LiYY 4 x 0.5 mm <sup>2</sup> or 2 x 0.5 mm <sup>2</sup>
Mounting	with mounting angle
Protection	IP 54
Dimension	Ø 134 x 175 mm
Survival speed	max. 60 m/s
Weight	0.3 kg
Mounting	Ø 35 x 35 mm

## Versions

As per 4.3515.5x.xxx, but:

### Product number 4.3515.50.000

#### Operating voltage

Heating	24 V DC, 24 W
---------	---------------

#### General

Electr. connection	3 m; LiYY 4 x 0.5 mm <sup>2</sup>
Instrument color	white

### Product number 4.3515.50.100

#### Operating voltage

Heating	24 V DC, 24 W
---------	---------------

#### General

Electr. connection	3 m; LiYY 4 x 0.5 mm <sup>2</sup>
Instrument color	black

### Product number 4.3515.51.000

#### Operating voltage

Heating	without Heating
---------	-----------------

#### General

Electr. connection	3 m; LiYY 4 x 0.5 mm <sup>2</sup>
Instrument color	white

### Product number 4.3515.51.100

#### Operating voltage

Heating	without heating
---------	-----------------

#### General

Electr. connection	3 m; LiYY 4 x 0.5 mm <sup>2</sup>
Instrument color	black

## Accessories

No accessories are available for this product.