

WIND

Combined Wind Transmitter

Part number: 4.3329.00.510

Compact wind transmitter construction for simple instrument mounting.

Wind vane, cup star and housing consist partially of fibre glass reinforced, housing brackets and mast boring of stainless steel and aluminium.



Specification

Part number: 4.3329.00.510

Wind speed	
Measuring range	1 ... 40 m/s 1 reed contact, 2 magnets
Resolution	typ. 2.3 Hz / m/s
Output	Potential-free pulses
Output load	max. 10 W, max. 0.5 A, max. 42 V DC
Wind direction	
Measuring range	10 ... 350 °
Output	Potentiometer 0 ... 1 k Ω 20 ° dead-zone in North
Temperature	
Meas. element	NTC, 10 k Ω
General	
Ambient temp.	-25 ... +60 °C, ice-free
Electr. connection	15 m cable, LiYCY 6x 0.25 mm ²
Mounting	onto mast tube \varnothing 30 mm
Protection	IP 54
Dimension	\varnothing 330 x 418 mm
Weight	1 kg
Fixing boring	\varnothing 31 x 26 mm

Versions

As per 4.3329.00.510, but:

Product number 4.3329.00.000

General	
Power supply	from display unit
Ambient temp.	-30 ... +60 °C
Electr. connection	20 m cable with plug
Mounting	auf Mastrohr Ø 30 mm
Dimension	Ø 200 x 450 mm
Weight	1 kg

Accessories

No accessories are available for this product.

