

Hygro-Thermo Transmitter compact

The data are output as electrical analogue signals The transmitters consist of a capacitive humidity element and a Pt 100 resistance thermometer. For outdoor installation we recommend the use of the weather- and thermal radiation shield.
Order no.: 1.1025.55 xxx

Specification

Part number: 1.1005.54.780

Temperature

Measuring range	-40 °C ... +85 °C
Meas. element	Pt 100 acc. to DIN IEC 60751 1/3 class B
Electr. output	MODBUS RTU

Rel. Humidity

Measuring range	0 % ... 100 % rel. h.
Accuracy	± 1.5 % rel. h. (@ 5 ... 95 % rel. h. and 10 ... 40 °C)
Meas. element	Capacitive
Electr. output	MODBUS RTU

Data output digital

Interface	RS485 MODBUS RTU-protocol
-----------	---------------------------


General




Power supply	5 ... 30 V DC
Electr. connection	plug connection
Protection	IP 30 for sensors IP 65 for electronic
Dimension	Ø 20 x 177 mm
Weight	0.45 kg

Versions

No other versions of this product are available.

Accessories

Product	Product name	Brief description
	Teflonfilter with gauze ZE 20 1.1005.54.901	This hood is placed over the sensor and protects the measurement element from coarse dirt.

	Sinter Filter ZE 21 1.1005.54.902	This basket is placed over the sensor and protects the measurement element from high wind speed (>5 m/s) and increased dust. A necessity for sensors in use in exposed areas, eg. in marine climates, desert, mountains.
	Wall Holder 1.1005.54.903	<p>for mounting the temperature (2.1280.xx.xxx) or hygrothermo Sensor (1.1005..xx.xxx) onto a wall, radiation- and precipitationprotected use (for ex. indoor)</p> <p>General</p> <p>Clamping range Ø 20 mm</p> <p>Mounting plate with with drillings 3 x Ø 6,5 mm</p> <p>Material plastic, grey flange</p> <p>Dimension 96 mm lang</p> <p>Weight 0.075 kg</p>
	Weather and Thermal Radiation Shield, compact 1.1025.55.000	<p>Protective case for the temperature and humidity sensors (2.1280.xx.xxx and 1.1005.54.xxx)sensor compact for outdoor installation without artificial ventilation.</p> <p>Material</p> <p>Laminations plastic, white</p> <p>Mast holder stainless stell</p> <p>General</p> <p>Mounting at tube Ø 35 ... 50 mm</p> <p>Dimension Ø 120 x 275 mm</p> <p>Weight 0.8 kg</p>



Weather and
Thermal
Radiation
Shield, compact
1.1025.55.100

Protective case for the preceding temperature sensor compact for outdoor installation with artificial ventilation.

Material	
Laminations	plastic, white
Mast holder	stainless stell
General	
Power supply	12V DC, 2 W
Electr. connection	5 m cable
Mounting	at tube Ø 35 ... 50 mm
Dimension	Ø 120 x 275 mm
Weight	0.8 kg

