

Wind Direction Transmitter "First Class"

Special characters are a defined and optimised, dynamic behaviour as well as:

- High measurement accuracy and resolution
- High damping with small distance constant
- Low starting value
- Low power consumption
- Simple mounting

The measuring value is available at the output as analogue signal. The output signal can be transmitted to display instruments, recording instruments, data loggers as well as to process control systems. For winter operation the instrument (4.3150.00.xxx) is equipped with an electronically regulated heating.

Specification

Part number: 4.3151.00.xxx

Wind direction

Measuring range	0 ... 360 °
Resolution	0.35 °
Accuracy	1 °
Starting value	0.5 m/s at 10 ° acc. to ASTM D 5096-96 0.2 m/s at 90 ° acc. to VDI3786 page 2
Distance constant	1.8 m acc. to ASTM D 5096-96
Damping ration	> 0.3 acc. to ASTM D 5096-96

Operating voltage

Electronic	3.3 ... 42 V DC
Heating	24 V AC/DC, 25 W

General

Ambient temp.	-50 ... +80 °C
Electr. connection	8 pol. plug connection
Mounting	onto mast tube \varnothing 1"
Material	aluminium, anodised
Protection	IP 55

Dimension	Ø 450 x 410 mm
Weight	0.7 kg
Mounting	Ø 35 x 25 mm

Versions

As per 4.3151.00.xxx, but:

Product number 4.3151.00.140

Data output analog

Wind direction 0 ... 20 mA

Operating voltage

Electronic 15 ... 24 V DC

Current consumption approx. 2.9 mA + I_{out}

Product number 4.3151.00.141

Data output analog

Wind direction 4 ... 20 mA

Operating voltage

Electronic 15 ... 24 V DC

Current consumption approx. 2.9 mA + I_{out}

Product number 4.3151.00.161

Data output analog

Wind direction 0 ... 10 V

Operating voltage

Electronic 15 ... 24 V DC

Current consumption approx. 2.9 mA + I_{out}

Product number 4.3151.00.173

Data output analog



Wind direction 0 ... 5 V

Operating voltage

Electronic 12 ... 24 V DC

Current consumption approx. 2.9 mA + I_{out}

Accessories

Product	Product name	Brief description
	Traverse for Wind Transmitters "First Class" 4.3174.00.000	For mounting the wind speed transmitter and wind direction transmitter jointly onto a mast. General Height 0.76 m Mounting on mast tube \varnothing 1,5'' Material aluminium, anodised (AlMgSi0.5) Sensor distance horizontal 0.6 m Sensor distance vertikal 0.2 m Weight 3 kg Mounting \varnothing 34 mm for First Class wind sensors
	Hanger 1m First Class 4.3184.01.000	The hanger is used for the lateral mounting of a wind transmitter, First Class type, onto a mast General Length 1 m Mounting at mast tube \varnothing 40 ... 80 mm Material aluminium (AlMgSi0.5) Weight 1.5 kg Mounting \varnothing 34 mm



Geovane
4.3190.00.900

The product set combines the precise wind vanes from Thies CLIMA with the advanced Geovane from Kintech Engineering. The Geovane uses GPS and the sun position to automatically determine the exact north direction 1° accurate. This combination ensures the highest accuracy of wind direction against the geographic north point as a reference.

- Geovane for automatic north correction
- 1° precise wind vanes from Thies CLIMA
- Wind vane and geovane are preconfigured
- Ideal e.g. for site surveys, power curve monitoring and meteorology

Wind direction

Measuring range 0 ... 380 °
Resolution 0.06° RS-485
 0.11° Analog voltage outputs
 0.06... 0.16° Frequency output

Accuracy 1°

Miscellaneous


Electrical input 0 ... 30 V

Operating voltage

Electronic 6 ... 12 V DC

General

Ambient temp. -25 ... +85 °C
Mounting Onto mast tube Ø34mm
Protection IP 67
Measuring time 1, 5, 10, 30, 60 seconds
Weight 0,815 kg



Northring for
First Class
Windfahne
509619

The adapter is used for the north alignment of a First Class Wind Direction Sensor.

General

Length 75 mm
Material Alluminum anodized (AlMgSi1)
Weight 0.25 kg
Mounting for mast Ø 35 mm
 for sensor Ø 35 mm

