

Rain Monitor

The precipitation drops are detected by a sensor area, and with wetting a contact is closed.

An integral heating system ensures ice and snow free operation in winter.

Complete with a mast fixing that can also be utilised for wall mounting.

Specification

Part number: 5.4106.0x.xxx

Precipitation

Collecting area	18 cm ²
Meas. principle	ceramic, capacitive sensor
Switch-on-delay	0.5 s
Switch-off-delay	approx. 15 s
Sensitivity	appr. 0.2 mm/h

Data output digital

Contact load	max. 26 VAC / 36 VDC
Switching output	max. 26 VAC / 36 VDC

General

Power supply	11 ... 28 VAC or 11 ... 32 VDC (max 0.75 A)
Ambient temp.	-30 ... +60 °C
Electr. connection	Item specific
Mounting	at mast tube or wall mounting
Material	Polycarbonat, Ceramic, stainless steel
Protection	IP 66
Dimension	77 x 49 x 37,5 mm
Weight	0.16 kg

Versions

As per 5.4106.0x.xxx, but:

Product number 5.4106.00.011

Data output digital

Electr. output	semiconductor relays, potential free, electrically isolated, normally open contact
----------------	---

General

Measuring value Precipitation yes / no
Cable 10m cable, 4 pol., cable shielded, uv-resistant

Product number 5.4106.00.100

Data output digital

Electr. output semiconductor relais, potential free, electrically isolated,
changeover contact

General

Measuring value Precipitation yes / no
Cable 3m cable, 5 pol.

Product number 5.4106.00.901

Data output digital

Electr. output semiconductor relais, potential free, electrically isolated,
normally open contact

General

Measuring value Precipitation yes / no
Cable 3m cable, 4 pol.

Product number 5.4106.01.011

Data output digital

Electr. output semiconductor relais, potential free, electrically isolated,
normally open contact

General

Measuring value Precipitation detected: (5Hz, 10 - 50Hz)
Cable 10m cable, 4 pol., cable shielded, uv-resistant

Accessories

No accessories are available for this product.

